



A200 rechargeable li-ion Battery USER MANUAL

WE STRONGLY RECOMMEND THAT YOU READ THIS INSTRUCTION BEFORE USING YOUR BEBOB A200 BATTERY! PLEASE KEEP THIS MANUAL FOR FUTURE REFERENCE

Features

- A high capacity battery which is compact and lightweight. Direct fitting to a camera via Gold Mount.
- Five-step LED power indicator (100% - 80% - 60% - 40% - 20%).
- Full Capacity Status LED (green over 70%; yellow between 50% and 70%; red under 50%)

Safety instructions

- Only for professional use! Keep batteries out of reach of children and personnel that has not been instructed in the use of high capacity Lithium-ion batteries!
- Use only with recommended charger.
- Keep the battery dry and do not immerse in water.
- Never open the case of the battery.
- Do not expose to temperature over 60°C.
- Do not expose the battery to fire! May explode if thrown into fire!
- Maximum Load 10.0A.
- Do not put the battery on a device when the red charging LED flashes.
- Handle with care! Do not throw! Do not drop!

Charging

- The bebob A200 battery can be charged with an external bebob charger (or equivalent) with Lithium-ion (Li-ion) charging ability.
- Approximate charge time may vary depending on charger and temperature.
- bebob A200 can be charged in ambient temperature for optimum performance at 10°C - 30°C.
- bebob A200 batteries can be recharged in any charge condition.

Discharging

- Maximum load is 10.0A. When using the battery with video or lighting equipment, power consumption of the equipment must be 10.0A or below. For the protection of the battery, a load of 10.0A or over may activate the internal protection circuit and stop supply of power. In this case the Fuse will self-rest after a couple of minutes
- The battery can be used in ambient temperature of - 20°C - + 55°C.

Storage

- Storage temperature range is - 20°C ~ + 35°C (<85% humidity).
- To store the battery for a long period (longer than 4 Weeks), the battery should be charged between 50% and 75%. The battery should be recharged every 4 Weeks.
- After storage some self-discharge will occur. Before re-use it is advisable to recharge the battery fully.

Warranty

- The A200 is covered by a 2 years unconditional warranty on all parts, except the cells.
- The cells are covered by a 1 year warranty, 70% of the original capacity.
- For warranty issues or if you have any additional questions, please contact the appropriate bebob distributor listed at www.bebob.de.

Disposal

- The A200 battery has to be disposed within a dedicated collection container for used device batteries. Please be aware that only empty batteries are allowed for disposal in collection containers. In case the battery is not completely discharged, precautions against a potential short-circuit have to be taken.

Specifications

Model	A200
Mount	Gold Mount
Capacity	6,0Ah; 296Wh
Voltage	14,4V DC
Maximum Output Voltage	16.8 V DC
End Voltage	12.0 V
Cells	Lithium-Ion Trimix made in Japan
Max. Discharge Current	10.0A
Twist D-Tap	14.4V unreg. Max. 35W
USB Port	5V, 1.0A
Fuel Gauge	5-Step LED
Weight	1.0 Kg
Dimensions (WXHxD)	94x144x58mm
Chargers	bebob, antonbauer
Charging time (bebob VS2/VS4)	4 Hours
Operating Temp. Range	Charge: + 10°C ~ + 30°C recommended Discharge:- 20°C ~ + 55°C Storage:- 20°C ~ + 35°C (<85% RH)

Transport as of April 1st 2016

- This Summary reflects our current Knowledge.

1. Transport by Commercial Airline / Carry-on Luggage

- A200 are forbidden in your **carry-on luggage**.

2. Transport by Commercial Airline / Checked-in Luggage

- A200 are forbidden in your **checked-in luggage**.

3. Transport as air-, road- and sea-freight

- Li-Ion batteries, and so bebob A200, when shipped by air, road or sea are classified as dangerous goods class 9 and subject to special UN certified packaging.
- Air transport authority training and authorisation (PK 1/ PK 2) are required for packing A200, for an air cargo shipment.
- **Li-Ion batteries for air cargo must have a state-of-charge of no more than 30% for shipping, means only one out of the five fuel gauge led lights up.**
- We recommend that you confirm with your carrier of choice, to determine any further restriction or local policies, before travelling. **You will find the actual regulation of your carrier of choice in the bebob transport information system www.fly-lithium.com,**

www.battery university.eu

CONFIRMATION UN 38.3 TESTING

WE HEREWITH CONFIRM THAT EACH BATTERY OF THIS TYPE IS PROVED TO MEET THE REQUIREMENTS OF EACH APPLICABLE TEST IN THE UN MANUAL OF TESTS AND CRITERIA, PART III, SUB-SECTION 38.3, REV. 5, Amend. 2

REPORT NO.:	BU-2016-04659-2-B1
Product:	LITHIUM ION BATTERY
Designation:	4S4P NCR18650GA (14.4V/13.6Ah/195.84Wh)
Article Number:	9073 · A200
Manufacturer:	bebob factory GmbH Höglwörthstr. 350 · D-81379 München · Germany

PERFORMED TESTS	RESULTS
38.3.4.1 Test 1: Altitude Simulation	passed
38.3.4.2 Test 2: Thermal Test	passed
38.3.4.3 Test 3: Vibration	passed
38.3.4.4 Test 4: Shock	passed
38.3.4.5 Test 5: External Short Circuit	passed
38.3.4.6 Test 6: Impact/Crush	not applicable
38.3.4.7 Test 7: Overcharge	passed
38.3.4.8 Test 8: Forced Discharge	not applicable

www.battery
university.eu
Batteryuniversity GmbH
Am Sportplatz 30 · D-63791 Karlstein am Main
Telefon +49 6188 99410-0 · Fax +49 6188 99410-20
mail@batteryuniversity.eu · www.batteryuniversity.eu

This confirmation is only valid in connection with the report mentioned above, and thus without signature. The listed regulation reflects the status at the time of the release of this confirmation.