


DECLARATION OF CONFORMITY UN38.3

We herewith confirm that each battery of this type is proved to meet the requirements of applicable tests in the UN Manual of Tests and Criteria ST/SG/AC.10/11/Rev.6/Corr.1, Part III, Sub-Section 38.3.

In the following, lithium battery test summary according to Sub-Section 38.3.5

- (a), (b) Manufacturer: bebob factory GmbH
Höglwörther Str. 350
81379 München
Germany
Phone: +49 (0)89 8563 485-18
Fax:
E-Mail: norbert.hans@bebob.de
Webpage: www.bebob.de
- Customer: bebob factory GmbH
Höglwörther Str. 350
81379 München
Germany
Phone: +49 (0)89 8563 485-18
Fax:
E-Mail: norbert.hans@bebob.de
Webpage: www.bebob.de
- (c) Test laboratory: Batteryuniversity GmbH
Am Sportplatz 30
63791 Karlstein am Main
Germany
Phone: +49 (0)6188 – 99410-0
Fax: +49 (0)6188 – 99410-20
E-Mail: mail@bu-lab.eu
Webpage: www.bu-lab.eu
- (d) Report reference no.: TZ_000176_UN
- (e) Date of test report: February 08, 2019
- (f) Description of devices under test:
- | | |
|----------------------------|-----------------------|
| (i) Type: | Lithium-ion batteries |
| (ii) Mass: | 544 g |
| (iii) Watt-hour rating: | 95.04 Wh |
| (iv) Physical description: | 4S2P NCR 18650GA |
| (v) Model numbers: | V98micro |
- (g) Performed tests:
- | | |
|-----------------------------|---------------|
| T.1 Altitude simulation: | Passed |
| T.2 Thermal test: | Passed |
| T.3 Vibration: | Passed |
| T.4 Shock: | Passed |
| T.5 External short circuit: | Passed |
| T.6 Impact/Crush: | Not performed |
| T.7 Overcharge: | Passed |
| T.8 Forced discharge: | Not performed |
- (h) Reference to assembled battery testing requirements: Not applicable
- (i) Applied standard: UN ST/SG/AC.10/11/ Rev.6/Corr.1
Recommendations of the TRANSPORT OF DANGEROUS GOODS, Manual of Tests and Criteria, Part III, section 38.3, Lithium metal and lithium ion batteries

(j) Signature: April 12, 2021 
Klaus Heck, Managing Director